







Designed to minimize seed loss without sacrificing speed, the Fantini G03 is tailor-made for an unprecedented harvest experience. Specially designed collecting pans and a high capacity auger retain seeds and maximize crop flow. Available in models from four to 18 rows, the G03 easily

adapts to any combine.

Thanks to a solid one-piece frame and tubular steel construction, the G03 is built to withstand the harshest field conditions. Simple, effective features including a one-piece row unit, transmission and PTO require minimal maintenance, yet can be easily repaired.







## **Additional Features and Accessories**

- Row Unit Oil Bath Gears: High-tech hardened steel gears lubricated in an oil bath for exceptional durability and longevity.
- Easily Adjustable Row Unit Chain Tension
- Adjustable Feeder Arm: Moves stalks towards the auger.
- Adjustable Divider Points: Ensure maximum efficiency in down crops, thereby reducing crop loss. They also fold back for convenient transport.
- **Side Guard Height:** Optimized to minimize crop loss and prevent sunflower heads from falling outside the header.
- Auger and Row Unit Transmission System: Allows the operating speed of the auger or row units to be changed by utilizing different sprockets. These can be easily changed in the field.





## **G03** SPECIFICATIONS

MODEL	NUMBER OF ROWS*	INTER-ROW DISTANCE**	
Rigid G03	From 4 to 16	30 in.	
	From 6 to 16	22 in.	
	From 6 to 18	20 in.	

## **GP** SPECIFICATIONS

MODEL	EFFECTIVE CUT	WIDTH	DEPTH	WEIGHT
GP	31.5 feet	32.2 feet	8.3 feet	6,922 lbs

\*Different number of rows available upon request \*\*Different row spacing available upon request





## fantini

15526 90th St. NE Drayton, ND 58225 Phone: 701-454-3875

Email: help@hamiltonsystemsinc.com

See more Fantini unrivaled solutions:



🚹 🌇 fantini-na.com